

Non-Slip Warranty

NEOLITH ASR

Neolith ASR is a very easy-to-clean non-slip surface. What follows are the results of the slip resistance pursuant to international standards.

STANDARD	SLIP RESISTANCE	
ANSI A326.3:2021 (DCOF)	≥ 0,60	
EN 16165:2021	Annex A	C
	Annex B	R11
	Annex C	C3

*Applications may vary depending on the standards in effect in the country where it is installed.

*The finish of this product mitigates slippage; the tone, look and shine are unique yet similar to the standard finish. For use exposed to footwear, the product requires a higher maintenance and cleaning frequency, especially white-based or cream models/colors.

The warranty covering this products is **3 years** after it is installed as long as the installation of the product meets the following conditions, as well as the legal terms detailed in the warranty document (<https://www.neolith.com/es/documentacion>).

- 01 Installation of flooring according to the "Neolith Flooring and Tiling Installation Manual" available at www.neolith.com
- 02 In-depth cleaning of residue following construction work without scratching the surface and without using abrasive products. Use of a cleaner for non-slip floors following the instructions in ANNEX 1.
- 03 Avoid soaking the non-slip surface with cement derivatives or cement adhesive, etc.
- 04 To maintain all the characteristics, you must follow the "Neolith Non-Slip Material Cleaning and Maintenance" manual, which is available at www.neolith.com. Please also see ANNEX I of this document for a summary.

THESIZE SURFACES SL


Pol. Ind. Camí Fondo, Supoi 8. C/Ibers 31 - 12550 Almassora (Spain)
+34 964 652 233 - warranty@neolith.com - www.neolith.com

Non-Slip Warranty

ANNEX I

CLEANING AND MAINTENANCE OF NEOLITH NON-SLIP MATERIAL

The importance of exhaustive post-work cleaning for non-slip flooring is worth highlighting. Thus, the following table is provided with cleaning products for guidance. Always follow the manufacturer's instructions.

			
Cement remains	DETERDEK PRO	ACID CLEANER/ FINE CEMENT REMOVER	DYSYCOTT
Epoxy remains	CR10	ELIMINADOR EPOXI	EPOXI RESIDUE REMOVER

For **extra cleaning**, the use of a non-aggressive descaling agent is recommended as well as the use of non-slip floor cleaners which help remove organic residue such as lime, mineral salts...

Table with different products for guidance in accordance with the type of cleaning to be done

			
Ordinary maintenance: CLEANER PRO Extra maintenance: PS87 PRO (using a brush with plastic bristles is recommended in both cases)	STONE CLEANER AND INTENSIVE CLEANING	Ordinary maintenance: FLOOR CLEANER Extra maintenance: TILE CLEANER (diluted 1:9)	Ordinary maintenance: FLOOR CLEANER Extra maintenance: TILE CLEANER (diluted 1:9)

THESIZE SURFACES SL

Pol. Ind. Camí Fondo, Supoi 8. C/Ibers 31 - 12550 Almassora (Spain)
+34 964 652 233 - warranty@neolith.com - www.neolith.com

Non-Slip Warranty

MODELS AVAILABLE

FUSION

PIETRA DI LUNA (ASR)

PIETRA DI OSSO (ASR)

PIETRA DI PIOMBO (ASR)

ARENA (ASR)

KRATER (ASR)

RETROSTONE (ASR)

SHILIN (ASR)

WULONG (ASR)

BASALT BLACK (ASR)

NERO ZIMBABWE (ASR)

NEW YORK - NEW YORK (ASR)

CLASSTONE

STRATA ARGENTUM (ASR)

THESIZE SURFACES SL

Pol. Ind. Camí Fondo, Supoi 8. C/lbers 31 - 12550 Almassora (Spain)
+34 964 652 233 - warranty@neolith.com - www.neolith.com